



Unterhaldenstrasse • CH-8717 Benken  
Tel. +41 (0)55 293 24 00 • [info@lignokustik.ch](mailto:info@lignokustik.ch)  
Fax +41 (0)55 293 24 01 • [www.lignokustik.ch](http://www.lignokustik.ch)

## Specification text

The following suggested text does not make any claim to completeness. Details and mounting methods are to be revised according to the project conditions. Variations of execution are subject to our review, based on our technical information (other wood species, RAL or NCS lacquer finishes).

### Lignokustik *beta N*

Acoustic wall and ceiling panels or door elements

Manufacture, supply and installation of sound-absorbing wall/ceiling panels.

Face: 6 mm thick, „V“ grooved Beta-Membrane B2 or B1

Axis spacing: 5 or 10 mm

Surface: veneered Maple or RAL/NCS colored

Surface finish: Clear fire retardant lacquer

Center: particle board B2 or B1

Rear: 3 mm thick perforated hardboard clad

Thickness: 22 mm +/- 0,5 mm

Length max. 3000 mm

Width: up to 600 mm,

Panel Layout: According to architect or designer's direction.

Panel Edges: Raw clean cut or matching veneer perimeter with or without continuous groove for slip feather.

Mounting Method: Panel elements are to be installed with at least a 3 mm wide joint between each unit with attention being paid to a properly aligned joint pattern.

Product: Lignokustik *beta N*

Manufactured by:

**Lignokustik AG**  
**Unterhaldenstrasse 32**  
**CH-8717 Benken**

**Tel.: 0041 (0)55 293 24 00**

**Fax 0041 (0)55 293 24 01**

**Email: [info@lignokustik.ch](mailto:info@lignokustik.ch)**

**Website: [www.lignokustik.ch](http://www.lignokustik.ch)**